

Model			LUMINA LS24		
Product Photo					
					
Backlight Module	Size		23.8"		
	Curved Ratio		N/A		
	Viewing area		527.04(W)×296.46(H) mm		
	Viewing angle		H:178° V:178°		
	Resolution		FHD 1920*1080		
	Refresh rate		120Hz		
	Aspect Ratio		16:9		
	Brightness	Defaulted(TYP)		280 (±30)	
		Max(TYP)		300(±30)	
	Default Color Temperature		6500K		
	Contrast Ratio		1000:1		
	Response Time	OC (GTG)		5ms	
	Display color		16.7M		
Colour Gamut (Coveraged)	sRGB		98%		
	NTSC		72%		
Electronics	I/O Prts (Standard)		VGA+HDMI+DP+AUDIO IN+AUDIO OUT+AC		
	VGA		*1 VGA		
	HDMI		*1 HDMI 1.4		
	DP		*1 DP 1.2		
	Speaker		3W*2		
	USB		USB B+2 USB A+2 USB C(data only),USB3.2 GEN 1		
	Power Supply		Internal power board		
	Power Consumption	Working		≤36W	
		Stand-by		≤0.5	
	Indicator Light Mode		Power on:Blue(LED)		
Structure	RGB light / Gaming Light		N/A		
	VESA		100*100mm		
	Size	Unit W/stand		540*495*216±5mm	
		Unit W/O stand		540*47.40*324.99±5mm	
		Packing Size		595*166*387mm	
	Weight	Net Weight		4.35KG	
		Gross Weight		5.50KG	
	Stand Functions	Angle (Forerake /Back-Lean)		Forerake : 6° Lean Back : 23°	
		Up and Down (Vertical)		135±5mm	
		Swivel (L/R)		Left/Right 30° ± 3°	
		Pivot (Rotation)		‘-90/ 90° (±3°)	
Assessory List			HDMI cable 1.5m, stand & base , power cable 1.5m,USB B-A cable 1.5m , Power UPS cable 1.5m		
Storage and working Environment		Firmware	Adjusting Color Temperature (Cold、Warm、User)		
			Low Blue Light Ajustement		
Working Temperature	-20°C~60°C		Flicker free		
Storage Temperature	0°C~40°C		6 Display model		
			FPS/RTS Game Mode with 1 key-switch		
			DCR 5Millions		
Working Humidity	10~85%RH		Multiple-Language Menu		
			FreeSync/ G-sync		
			Black level		
Storage Humidity	5~90%(No Freezing under 40°C)		OD		
			HDR		
Altitudes	≤5000m		/		
Panel grade			/		
A++ grade Panel			/		